

Semi Rules

Must be street legal and have valid license plates and insurance.

18in. hitch height, 48in. from hitch point to rear of the rear drive (max.)

DOT approved tires

All air bags must be inflated when checking hitch

1.mitchell@
enterpriseengine.com

Street Stock Truck – 6200# 4WD

1. Trucks must be street legal, with current license plates and current insurance card required, to enter class
2. Trucks must be driven to the pull. (No hauling trucks in on trailers allowed.)
3. Street legal DOT approved tires only. (No Baja Claw tires or Boggers permitted.)
4. Must pull from rear bumper or Reese style hitch. - 1" steel plate, 3^{3/4}" diameter hole, or clevis (No altered hitches permitted.) Max.-26" hitch height.
5. No front weight brackets.
6. Front bumper must be Stock appearing front bumper. (No tube or solid bumpers.)
7. Weights allowed in bed only. (Must be secured.)
8. Must have tailgate.
9. No homemade flat beds –(aftermarket flat beds are permitted.)
10. Aftermarket carburetors allowed with a max. 750 cfm.
11. Headers allowed, with street legal exhaust that must exit behind rear tires.
12. No aluminum intakes or heads unless OEM.
13. No blocked rear suspension and no clamped rear springs. Suspension must have 2" travel.
14. One safety chain per drive shaft required. (Fire extinguisher recommended.)
15. One hook per vehicle per class.
16. All Judges Decisions are final. (If we feel you do not meet these rules, you will be placed in the Modified Street Stock class.)

15,000 lb Farm Stock Tractor Rules

1. All tractors must be stock in appearance from front to rear. All hoods, grills, fenders, and frames will be stock appearing for that make and model of tractor. Front ends must be factory wide or after market replacement and will be located in the factory position. Tractors must have stock block or its replacement. All tractors must use the fuel it was designed for. Max- P-pump.
2. Tractors must have a draw bar with 3 3/4" minimum hole, located no more than 20" in height, and no less than 18" from center of rear axle.
3. If weights, excess fluid, or any parts fall off during the pull, that pull will be disqualified.
4. Drivers must be a minimum of 18 years old to pull in this class.
5. No more than one person permitted on a tractor. NO RIDER
6. Front weights must be on a factory weight bracket bolted directly on front of tractor.
7. Rear weights allowed but cannot interfere with hooking and unhooking of the sled
8. Drivers must start with a tight chain. Jerking of the sled will not be permitted.
9. All tractors are subject to hitch height and weight checks
10. No cut tires.
11. 3000 rpm limit.
12. Must have working PTO and hydraulics
13. Wheelie bars are recommended but not required
14. All decisions of the track officials are final.

HOLMES COUNTY FAIR
6200 LB Modified Street Stock Rules:

ENGINES & DRIVE TRAIN:

1. Cast iron blocks only, aluminum intakes, any cast iron or conventional type aluminum cylinder heads permitted. No Pro Stock type cylinder heads, sheet metal, or tunnel ram intakes permitted. No dry sump oiling systems.
2. A 585 cu.in. Limit will be enforced.
3. [REDACTED]
4. Open headers permitted must exit down and back.
5. Engine must be same make as truck and the back side of block must be at least 15" behind the center of front axle.
6. Transmission, transfer case front, and rear end must be OEM, 1 ton or less.
7. Heavy duty aftermarket drive train parts can be used in OEM housings.

CHASSIS:

1. Factory frames only, no tube chassis.
2. Traction bars are permitted.
3. Solid or block suspension permitted front and rear

WEIGHTS:

1. Max wheel base is 140 center to center. Front weight bracket 60" from center of front axle to furthest point forward

HITCH:

1. Hitch must be a minimum of 36" from the center of the rear axle and a maximum of 24"-26" high depending on eve.
2. Hitch can be adjustable, but must be stationary in all directions when pulling.
3. Hitch must not be above frame rails, pivot point can be no farther forward than center of rear axle.
4. Hitch must be 3 3/4 x 3 hole, min 3 3/4 x 1" thick.

TRUCK:

1. Cab must have factory sheet metal and windows.
2. Must have good solid bed floors.
3. Flat beds are permitted as long as they are factory built or heavier.
4. Fiberglass hoods and hood scoops are permitted.
5. Batteries and fuel tanks must be in stock location or in bed.

TIRES:

1. Any street legal DOT approved tire.
2. Maximum tire size is 36" tall x 16" wide.
3. No cut or sharpened tires allowed.

SAFETY:

1. No nitrous or any pressurized fuels.
2. Pump gas or racing gas only, no alcohol or nitro permitted.
3. Drive shaft loops, U- Joint shields, blow proof bell housing or transmission blanket, and kill switches are required.

*** TRUCKS WILL BE CHECKED AT STAGING AREA FOR SAFETY EQUIPMENT AND CARBURATOR.**

2008 Hot Farm Stock Rules

1. All tractors must be stock in appearance from front to rear. All hoods, grills, fenders, and frames will be stock appearing for that make and model of tractor. Front ends must be factory wide or after market replacement and will be located in the factory position. Homemade front ends are permitted. Tractors must have stock block or its replacement. All tractors must use the fuel it was designed for. Max- P-pump.
2. Tractors must have a draw bar with 3" minimum hole, located no more than 20" in height, and no less than 18" from center of rear axle.
3. If weights, excess fluid, or any parts fall off during the pull, that pull will be disqualified.
4. Drivers must be a minimum of 18 years old to pull in this class.
5. No more than one person permitted on a tractor. NO RIDERS!!
6. All tractors must have a safety kill switch and/or shutoff that are accessible to both the driver and the rear of the tractor. Tractors must have a double spring-loaded throttle. Tractors must have a 2 ½ lb. minimum dry powder fire extinguisher. Drivers must wear a helmet when pulling.
7. Tractors in this class will have wheelie bars and must be able to support the weight of the tractor according to NTPA specs. NTPA style roll cages are recommended, but a roll bar is required.
8. One turbo, no larger than 3 1/2 x 3 maximum. No external alterations. Exhaust pipes off of turbos must have cross bolts with minimum grade 5 hardness and 5/16 diameter.
9. Flywheel blankets are required. Steel flywheels are required, no cast flywheels.
10. Front weights cannot extend more than 13' from center of rear axle to the front of the weights. Rear weights cannot extend more than 6" past rear of back tire and in no way interfere with the hooking and unhooking of the sled. No wheel weights are permitted.
11. Drivers must start with a tight chain. Jerking of the sled will not be permitted.
12. All tractors are subject to random safety checks, hitch height, and weight checks.
13. Maximum tire size is 20.8-38, Cut tires are permitted.
14. All decisions of the track officials are final.